

## ContainerPower Energy Solutions

# Communication base station electricity billing plan



## Overview

---

Can communication and power coordination planning improve communication quality of service?

Our study introduces a communications and power coordination planning (CPCP) model that encompasses both distributed energy resources and base stations to improve communication quality of service.

How does a base station work?

As shown in Figure S3 each user accesses a base station, and the BS then allocates a channel to each new user when there is remaining channel capacity. If all of the channel capacity of a BS is occupied, a user cannot access this BS and must instead access another BS that is farther away.

What is the access mechanism between EMCs and BSS?

To describe the access mechanism between the EMCs and the BSs, we introduce an  $N_{bs} \times N_{mg}$  connection matrix  $A$ , where  $N_{mg}$  is the EMCs number and  $N_{bs}$  is the number of power towers which is also the number of candidate locations for base stations. It is not necessary for all power towers to be selected as communication power sharing towers.

Does the power consumption of a BS increase linearly?

The power consumption of BS  $n$  increases linearly with its total transmit power, including all subcarriers. Intuitively, the power load of a BS has a linear relationship with its communication load. In this paper, the BS access scheme is modelled via OFDMA. Note that the use of OFDMA is convenient for performance evaluation.

How many Bs can an EMC access?

Constraint (6) means that each EMC can access only one BS. Constraint (7) means that the number of EMCs accessing BS  $n$  is equal to the total state variables of the  $n$ th column of the matrix  $A$ . The capacity of each BS is  $D_c a$

p.

## Communication base station electricity billing plan

---

### Contact Us

---

For catalog requests, pricing, or partnerships, please visit:  
<https://www.websparafotografos.es>